


C-411 HANGER FOR C-411 OR C-412 TRACK

INSTRUCTION SHEET




PARTS LIST

C-411 HANGER
(2 PER DOOR)



C-411 TOP PLATE
(1 PER HANGER)



C-411 SPINWHEEL
(1 PER HANGER)



C-411 T-BOLT
(1 PER HANGER)




5/16" HEX NUT &
LOCK WASHER
(2 PER HANGER)



#10 X 1-3/4"
FLATHEAD SCREWS
(4 PER HANGER)



EXTRUDED
ALUMINUM TRACK



SPECIFICATIONS:


-LOAD CAPACITY:
150 LBS PER DOOR.

-QUICK RELEASE
HANGER ASSEMBLY.

-HEAVY-DUTY PRECISION
BALL BEARING WHEELS
WITH NYLON TIRE.

-EASY LEVELING AND
HEIGHT ADJUSTMENT
ACCOMPLISHED BY
HAND.

-FOR BY-PASSING,
BI-PARTING, POCKET,
AND SURFACE
MOUNT/BARN STYLE
APPLICATIONS.



STEP 1

DETERMINE DOOR SIZE/HEADER HEIGHT BASED ON DIMENSIONS SHOWN IN
DETAIL VIEWS AND CLEARANCE REQUIRED BELOW DOOR. INSERT C-411
HANGERS INTO TRACK AND SECURE TRACK TO HEADER

STEP 2

A) LOCATE CLEARANCE HOLE FOR HANGER STUD 3-1/2" FROM EACH EDGE
OF DOOR. DRILL WITH 3/8" BIT AT LEAST 2" DEEP. IF USING KNC CAS-2
DOOR STOP, LOCATE CLEARANCE HOLE 5-1/2" FROM EDGE OF DOOR.
B) CENTER TOP PLATE OVER HOLE, MARK SCREW HOLE LOCATIONS AND
PRE-DRILL WITH 1/8" BIT AT LEAST 1-1/2" DEEP.

STEP 3

PREPARE TOP PLATE ASSEMBLIES (2 SETS) AS FOLLOWS: TOP PLATE (1)
WITH T-BOLT(1), 5/16" HEX NUTS AND LOCK WASHERS (1 OR 2) AND
SPIN-WHEEL (1). ONE NUT FOR LOCKING ADJUSTMENT IN PLACE,
OPTIONAL SECOND NUT FOR PREVENTING DISCONNECTION FROM
HANGER. (RECOMMENDED)

STEP 4

MOUNT TOP PLATE ASSEMBLIES ON DOOR AND SECURE WITH
#10 X 1-3/4" FLATHEAD SCREWS (4 PER TOP PLATE).

STEP 5

INSTALL OPTIONAL PRODUCTS IF PURCHASED SUCH AS GUIDE CHANNELS,
CUP PULLS, DOOR LOCKS, ETC. INDIVIDUAL INSTRUCTIONS ARE PROVIDED
WITH THE RESPECTIVE PRODUCT.




STEP 6

PLACE DOOR UNDER TRACK AND LIFT TO ENGAGE T-BOLTS INTO HANGER
SLOTS.

STEP 7

ADJUST DOOR HEIGHT AND PLUMB VIA SPINWHEEL. LOCK ADJUSTMENT
BY TIGHTENING HEX NUT AGAINST TOP PLATE. PREVENT UNINTENTIONAL
DISCONNECTION OF DOOR FROM HANGER BY LOCKING OPTIONAL SECOND
HEX NUT AGAINST UNDERSIDE OF HANGER. (RECOMMENDED)

NOTE: MINIMUM CLEARANCE OF 1/2" REQUIRED BETWEEN DOOR AND
FASCIA FOR DISENGAGEMENT.



K.N. CROWDER MFG. INC.

1220 BURLOAK DRIVE
BURLINGTON, ONTARIO, CANADA, L7L 6B3
TELEPHONE: 905-315-9788 - FAX: 905-315-8090
TOLL FREE FAX: 1-800-567-0123

K.N. CROWDER INC.

210 EIGHTH STREET SOUTH
LEWISTON, NEW YORK, U.S.A. 14092
TELEPHONE: 1-716-754-8247
TOLL FREE FAX: 1-800-567-0123

WEBSITE: www.kncrowder.com -- E-MAIL: customerservice@kncrowder.com